Assignment 1

- Write heapsort
 - a method that takes an array of ints and sorts it by heapsort
 - overview of heapsort
 - sorting using a heap
 - heap binary tree where each node has smaller value than its children
 - heap is constructed directly in the array
 - children of the node i are 2*i+1 and 2*i+2

```
void heapSort(int[] a) {
  heapify(a, a.length);
  end = a.length - 1;
  while (end > 0) {
    swap(a[end], a[0]);
    siftDown(a, 0, end-1);
  end--;
```

Assignment 2

- Write quicksort
- Compare speed of both algorithms
 - create a big array and fill it with random data

```
java.util.Random r = new Random()
x = r.nextInt();
```

calculate necessary time

```
long before = System.nanoTime();
....measured part....
long after = System.nanoTime();
long dobaBehuNanos = after - before;
```

Assignment 3 – for fast ones

- Create a hash table
 - write the class MyHashTable, which serves as a hash table
 - keys String
 - values Object
 - methods at least
 - Object get(String key)
 - void set(String key, Object value)
 - iterator over keys
 - variant for the "brave ones" create the hash table as e generic type (i.e. keys and values are generic)
 - create a program that counts number of words in a given file

Tests...

Test 1



What is printed out

```
public interface Test {
  public static void main(String[] argv) {
    System.out.println("Hello");
  }
}
```

- A Cannot be compiled, the compiler prints out a message about bad syntax
- B Can be compiled but not executed, since main cannot be in an interface
- C Can be compiled and prints out Hello, since static methods can be in interfaces

Test 2



What is printed out

```
public enum Test {
   RED, GREEN, BLUE;

  public static void main(String[] argv) {
    System.out.println("Hello");
   }
}
```

- A Cannot be compiled, the compiler prints out a message about bad syntax
- B Can be compiled but not executed, since main cannot be in an enum
- C Can be compiled and prints out Hello

