

Java

Strings

String

- instances of `java.lang.String`
 - compiler works with them *almost* like with primitive types
 - String constants = instances of the String class
 - **immutable!!!**
 - modifications via classes `StringBuffer`, `StringBuilder`
 - will be later
 - operator `+`
 - String concatenation
 - if there is at least a single String in a `+` expression -> all is converted to Strings and concatenated
 - method `toString()`
 - defined in the class `Object`
 - commonly overridden
- operators priority still holds

Strings

- What is printed out?

```
System.out.println("hello " + 1 + 2)
```

- And now?

```
System.out.println(1 + 2 + " hello")
```

java.lang.String

- constructors

```
String();  
String(char[] value);  
String(byte[] bytes);  
String(byte[] bytes, String charsetName);  
String(String value);  
String(StringBuffer value);  
String(StringBuilder value);
```

java.lang.String

- **methods**

- `int length();`
- `char charAt(int index);`
 - `IndexOutOfBoundsException`
- `boolean equals(Object o);`
 - **compares Strings**
 - **== compares references**

```
String a = new String("hello");  
String b = new String("hello");  
System.out.println(a==b); // false  
System.out.println(a.equals(b)); //true
```

java.lang.String

- methods

- `int compareTo(String s);`
 - **lexicographical comparison**
- `int compareToIgnoreCase(String s);`
- `int indexOf(char c);`
- `int indexOf(String s);`
 - **return -1, if there is no such char or substring**
- `String substring(int beginIndex);`
- `String substring(int beginIndex, int endIndex);`
- `String replaceFirst(String regexp, String repl);`
- `String replaceAll(String regexp, String repl);`

Strings

- methods (cnt.)
 - `String join(CharSequence delimiter, CharSequence... elements);`
 - since Java 8
- methods can be called on String constants also

```
String s;  
...  
if ("ahoj".equals(s)) {  
    ...  
}
```

Java

Wrapper types

Wrappers

- immutable
- Integer
 - constructors – deprecated since Java 9
 - ~~Integer(int value)~~
 - ~~Integer(String s)~~
 - methods
 - `int intValue()`
 - `static Integer valueOf(int I)`
 - can cache values
 - `static int parseInt(String s)`
 - ...
- other wrapper types similarly

Java

More about methods

Local variables

- definition anywhere in body
- visible in a block
 - see the first lecture
- no initialization
- can be defined as **final**
 - constants
 - no other modifier can be used
- *effectively final*
 - defined without **final** but the value is never changed after it is initialized

Type inference for loc. vars

- since Java 10
- only for local variables

```
var s = "hello";  
var list = new ArrayList<String>();
```

- var – reserved type name
 - it is not a keyword
- requires initialization
- not always applicable
 - cannot be used with
 - null
 - array initialization
 - lambdas

Method overloading

- several methods with the same name but different parameters
 - different number and/or type

```
public void draw(String s) {  
    ...  
}  
public void draw(int i) {  
    ...  
}  
public void draw(int i, double f) {  
    ...  
}
```

- cannot overload just by a different return type

Recursive calls

- recursion – a method calls itself

```
public static long factorial(int n) {  
    if (n == 1) return 1;  
    return n * factorial(n-1);  
}
```

- be aware about termination
- non terminated -> stack overrun
 - a size of the stack can be set

Java

Exceptions

Exceptions

- errors reporting and handling
 - an exception represents an error state of a program
- exception = an instance of `java.lang.Throwable`
- two subclasses – `java.lang.Error` and `java.lang.Exception`
 - specific exceptions – children of the above two classes
- `java.lang.Error`
 - "unrecoverable" errors
 - should not be caught
 - e.g. `OutOfMemoryError`
- `java.lang.Exception`
 - recoverable errors
 - should (has to) be caught
 - e.g. `ArrayIndexOutOfBoundsException`

Exception handling

- **statement** `try/catch/finally`

```
try {  
    ... // a block of code where an exception  
        // can happen and we want to handle it  
} catch (Exception1 e) {  
    // handling of exceptions with the  
    // Exception1 type and its subtypes  
} catch (Exception2 e) {  
    // handling of exceptions with the  
    // Exception2 type and its subtypes  
} finally {  
    // executes always  
}
```

Exception handling

- if the exception is not caught in a block where it occurs, it propagates to the upper block
- if the exception is not caught in a method, it propagates to the calling method
- if the exception reaches `main()` and it not caught, it terminates the virtual machine
 - information about the exception is printed

try/catch/finally

- catch or finally can be omitted
 - but both cannot be omitted

Extended try (since Java 7)

- interface **AutoClosable** and extended **try**

- example:

```
class Foo implements AutoClosable {  
    ...  
    public void close() { ... }  
}
```

```
try ( Foo f1 = new Foo(); Foo f2 = new Foo() ) {  
    ...  
} catch (...) {  
    ...  
} finally {  
    ...  
}
```

- at the end of **try** (normally or by an exception), **close()** is always called on all the objects in the **try** declaration
 - called in the reverse order than declared

Extended try

- both catch and finally can be omitted together

```
try (Resource r = new Resource()) {  
    ...  
}
```

- since Java 9, (effectively) final variables can be used in extended try

```
final Resource resource1 = new Resource("res1");  
Resource resource2 = new Resource("res2");  
  
try (resource1; resource2) {  
    ...  
}
```

„multi“ catch (since Java 7)

```
class Exception1 extends Exception {}  
class Exception2 extends Exception {}
```

```
try {  
    boolean test = true;  
    if (test) {  
        throw new Exception1();  
    } else {  
        throw new Exception2();  
    }  
} catch (Exception1 | Exception2 e) {  
    ...  
}
```

Exception declaration

- a method that can throw an exception must either
 - catch the exception, or
 - declare the exception via `throws`

```
public void openFile() throws IOException {  
    ...  
}
```

- it is not necessary to declare following exceptions
 - children of `java.lang.Error`
 - children of `java.lang.RuntimeException`
 - it extends `java.lang.Exception`
 - **ex.** `NullPointerException`,
`ArrayIndexOutOfBoundsException`

Throwing exceptions

- `statement throw`
 - throws (generates) an exception
 - "argument" – a reference to `Throwable`

```
throw new MyException();
```

- existing exceptions can be thrown but, commonly, own ones are used
- exceptions can be “re-thrown”

```
try {  
    ...  
} catch (Exception e) {  
    ...  
    throw e;  
}
```


Re-throwing

```
class Exception1 extends Exception {}  
class Exception2 extends Exception {}
```

```
public static void main(String[] args) throws  
Exception1, Exception2 {  
    try {  
        boolean test = true;  
        if (test) {  
            throw new Exception1();  
        } else {  
            throw new Exception2();  
        }  
    } catch (Exception e) {  
        throw e;  
    }  
}
```

- since Java 7 exceptions “remember” their types
- with Java 6, this cannot be compiled
 - it would require `throws Exception`

java.lang.Throwable

- has the field (private) typed `String`
 - contains a detailed description of the exception
 - method `String getMessage()`
- **constructors**
 - `Throwable()`
 - `Throwable(String msg)`
 - `Throwable(String msg, Throwable cause)`
 - `Throwable(Throwable cause)`
- **methods**
 - `void printStackTrace()`

Own exceptions

```
public class MyException extends Exception {
    public MyException() {
        super();
    }
    public MyException(String s) {
        super(s);
    }
    public MyException(String s, Throwable t) {
        super(s, t);
    }
    public MyException(Throwable t) {
        super(t);
    }
}
```

Chains of exceptions

```
...  
try {  
    ...  
    ...  
} catch (Exception1 e) {  
    ...  
    throw new Exception2 (e);  
}  
...
```

- throwing an exception as a reaction to another exception
 - it is common
 - reacting to a “system” exception by an “own” one

Suppressing exception

- in several cases an exception can suppress another one
 - it is not chaining of exceptions!
 - typically it can happen
 - if an exception occurs in the **finally** block
 - in the extended **try** block (Java 7)
- **Throwable[] getSuppressed()**
 - method in **Throwable**
 - returns an array of suppressed exceptions

JAVA

Inner classes

Inner classes

- defined in the body of another class

```
public class MyClass {  
    class InnerClass {  
        int i = 0;  
        public int value() { return i; }  
    }  
    public void add() {  
        InnerClass a = new InnerClass();  
    }  
}
```

Inner classes

- the inner class can return a reference to the outer class

```
public class MyClass {
    class InnerClass {
        int i = 0;
        public int value() { return i; }
    }
    public InnerClass add() {
        return new InnerClass();
    }
    public static void main(String[] args) {
        MyClass p = new MyClass();
        MyClass.InnerClass a = p.add();
    }
}
```


Hiding inner class

- inner class can be `private` or `protected`
- access to it via an interface

```
public interface MyIface {
    int value();
}
public class MyClass {
    private class InnerClass implements MyIface {
        private i = 0;
        public int value() {return i;}
    }
    public MyIface add() {return new InnerClass();}
}
...
public static void main(String[] args) {
    MyClass p = new MyClass();
    MyIface a = p.add();
    // error - MyClass.InnerClass a = p.add();
}
```

Inner classes in methods

- an inner class can be defined in method or just a block of code
- visible just in the method (block)

```
public class MyClass {
    public MyIface add() {
        class InnerClass implements MyIface {
            private i = 0;
            public int value() {return i;}
        }
        return new InnerClass();
    }
    public static void main(String[] args) {
        MyClass p = new MyClass();
        MyIface a = p.add();
        // error - MyClass.InnerClass a = p.add();
    }
}
```

Anonymous inner classes

```
public class MyClass {
    public MyIface add() {
        return new MyIface() {
            private int i = 0;
            public int value() {return i;}
        };
    }

    public static void main(String[] args) {
        MyClass p = new MyClass();
        MyIface a = p.add();
    }
}
```

Anonymous inner classes

```
public class Wrap {
    private int v;
    public Wrap(int value) { v = value; }
    public int value() { return v; }
}

public class MyClass {
    public Wrap wrap(int v) {
        return new Wrap(v) {
            public int value() {
                return super.value() * 10;
            }
        };
    }

    public static void main(String[] args) {
        MyClass p = new MyClass();
        Wrap a = p.wrap(5);
    }
}
```

Anon. inner classes: initialization

- elements outside an anon. in. class necessary in the anon. in. class – **final**
- without `final` – compile-time error
- since Java 8 - “**effectively**” `final` is enough
 - i.e. declared without the `final` modifier,
 - but there are no changes to the particular element

```
public class MyClass {  
    public MyIface add(final int val) {  
        return new MyIface() {  
            private int i = val;  
            public int value() {return i;}  
        };  
    }  
}
```

- till Java 7 **final** is necessary here
- since Java 8 **final** can be omitted
 - as there are no changes to **val**

Anon. inner classes: initialization

- anon. inner classes cannot have a constructor
 - because they are anonymous
- object initializer

```
public class MyClass {
    public MyIface add(final int val) {
        return new MyIface() {
            private int i;
            {
                if (val < 0)
                    i = 0;
                else
                    i = val;
            }
            public int value() {return i;}
        };
    }
}
```

Relation of inner and outer class

- the instance of an inner class can access **all** elements of the instance of the outer class

```
interface Iterator {
    boolean hasNext();
    Object next();
}

public class Array {
    private Object[] o;
    private int next = 0;
    public Array(int size) {
        o = new Object [size];
    }
    public void add(Object x) {
        if (next < o.length) {
            o[next] = x;
            next++;
        }
    }
} // cont....
```

Relation of inner and outer class

```
// cont....
private class AIterator implements Iterator {
    int i = 0;
    public boolean hasNext() {
        return i < o.length;
    }
    public Object next() {
        if (i < o.length)
            return o[i++];
        else
            throw new NoSuchElementException();
    }
}

public Iterator getIterator() {
    return new AIterator();
}
}
```


Relation of inner and outer class

- a reference to the instance of the outer class
 - `OuterClassName.this`
 - **previous example – classes `Array` and `AIterator`**
 - the reference to the instance of `Array` from `Array.AIterator` – `Array.this`

Relation of inner and outer class

- creation of the instance of an inner class outside of its outer class

```
public class MyClass {  
    class InnerClass {  
    }  
    public static void main(String[] args) {  
        MyClass p = new MyClass();  
        MyClass.InnerClass i = p.new InnerClass();  
    }  
}
```

- an instance of an inner class cannot be created without an instance of its outer class
 - instances of an inner class always have a (hidden) reference to an instance of its outer class

Inner classes in inner classes

- from an inner class, an outer class on any level of nesting can be accessed

```
class A {
    private void f() {}
    class B {
        private void g() {}
        class C {
            void h() {
                g();
                f();
            }
        }
    }
}
public class X {
    public static void main(String[] args) {
        A a = new A();
        A.B b = a.new B();
        A.B.C c = b.new C();
        c.h();
    }
}
```

Inheriting from inner classes

- a reference to an instance of the outer class has to be **explicitly** passed

```
class WithInner {
    class Inner {}
}
class InheritInner extends WithInner.Inner {
    InheritInner(WithInner wi) {
        wi.super();
    }
    // InheritInner() {} // compile-time error

    public static void main(String[] argv) {
        WithInner wi = new WithInner();
        InheritInner ii = new InheritInner(wi);
    }
}
```

Nested classes

- defined with the keyword `static`
- do not have a reference to an instance of its outer class
- can have static elements
 - inner classes cannot have static elements
- do not need an instance of the outer class
 - they do not have the reference to it
- in fact, they are regular classes just placed in the namespace of the outer class

```
public class MyClass {  
    public static class NestedClass {  
    }  
  
    public static void main(String[] args) {  
        MyClass.NestedClass nc = new MyClass.NestedClass();  
    }  
}
```

Nested classes

- can be defined in an interface
 - inner classes cannot be

```
interface MyInterface {  
    static class Nested {  
        int a, b;  
        public Nested() {}  
        void m();  
    }  
}
```

Inner classes and .class files

- inner (or nested) class – own .class file
- `OuterName$InnerName.class`
 - `MyClass$InnerClass.class`
- **anonymous inner classes**
 - `OuterName$SequentialNumber.class`
 - `MyClass$1.class`
- **a nested class can have the `main` method**
 - **launching:** `java OuterName$NestedName`

Reasons for using inner classes

- hiding an implementation
- access to all elements of the outer class
- “callbacks”
- ...



Slides version J03.en.2020.01

This slides are licensed under a [Creative Commons Attribution-NonCommercial 4.0 International License](https://creativecommons.org/licenses/by-nc/4.0/).